



Standard Stock Specifications

Grade	Condition	Thickness	Width	Length
A 36	As Rolled	3/16" to 12-1/2"	60", 72", 96"& 120" ^A	240" & 480"
A 572-50	As Rolled	3/16" to 4"	60", 72", 96"& 120" ^A	240" & 480"
A 572-42	As Rolled	Above 4" to 6"	96" & 120"	240" ^B
A 588 / A 242	As Rolled	3/16" to 2"	96"	240" & 480"
A 633-C	Normalized	1/4" to 4"	96" & 120"	240" & 480" ^B
A 514	Quenched & Tempered	3/16" to 7"	96" & 120"	240" & 480" ^B
A 709	As Rolled	3/16" to 4"	60", 72", 96"& 120" ^A	240" & 480"
SA 516	As Rolled	3/16" to 1-1/2"	96" & 120"	240" & 480" ^B
SA 516	Normalized	3/16" to 12-1/2"	96" & 120"	240" & 480" ^B
SA 516	HIC	1/2" to 2"	96" & 120"	240" & 480"
SA 387-11	Normalized & Tempered	3/16" to 6"	96" & 120"	240" & 480" ^B
SA 387-22	Normalized & Tempered	3/16" to 4"	96" & 120"	240" & 480" ^B
SA 537-1	Normalized	1/4" to 4"	96" & 120"	240" & 480" ^B
API 2H	Normalized	1/4" to 4"	96" & 120"	240" & 480" ^B
API 2W	TMCP	1" to 2"	96" & 120"	240" & 480"
ABS A	As Rolled	3/16" to 4"	96" & 120"	240" & 480" ^B
ABS EH/DH	Normalized	1/4" to 4"	96" & 120"	240" & 480" ^B
AR 400	Quenched & Tempered	3/16" to 4"	96"	288"
AR 500	Quenched & Tempered	1/4" to 2"	96"	288"
T 21 / EHSP / 500TI	As Quenched	1/4" to 2"	96"	288"
4140	As Rolled, Annealed, and Pre-Hard	1/4" to 12"	96"	240" & 480" ^B
1045	As rolled	3/16" to 1-1/2"	96" & 120"	240" & 480"

Note: Additional grades, conditions, thicknesses, and plate sizes are available upon request

^A Availability varies depending on thickness

^B Length restrictions exist, depending on plate weight and mill capabilities